

**Prepared For:**

North-West Fire CO.  
Rosenbauer Minnesota  
PO Box 57  
Lyons, SD 57041-0057  
(605)543 - 5591  
Reference ID: 14/26 4dr

**Presented By:**

CRAWFORD TRKS. & EQUIP.  
Brian Brakefield  
3601 - 6TH AVE SOUTHEAST  
ABERDEEN SD 57401 -  
(605)225-6200

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

**Model Profile**  
**2025 HV507 SFA (HV507)**

<b>AXLE CONFIG:</b>	4X4
<b>APPLICATION:</b>	Fire/Pumper
<b>MISSION:</b>	Requested GVWR: 40000. Calc. GVWR: 40000. Calc. GCWR: 80000 Calc. Start / Grade Ability: 31.47% / 3.40% @ 55 MPH Calc. Geared Speed: 75.5 MPH
<b>DIMENSION:</b>	Wheelbase: 201.00, CA: 82.10, Axle to Frame: 75.00
<b>ENGINE, DIESEL:</b>	{Cummins L9 380} EPA 2024, 380HP @ 2100 RPM, 1150 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 380 Peak HP (Max), (RATED FOR EMERGENCY VEHICLES ONLY)
<b>TRANSMISSION, AUTOMATIC:</b>	{Allison 3000 EVS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor
<b>CLUTCH:</b>	Omit Item (Clutch & Control)
<b>AXLE, FRONT DRIVING:</b>	{Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel Mounting
<b>AXLE, REAR, SINGLE:</b>	{Dana Spicer S26-190} Single Reduction, 26,000-lb Capacity, R Wheel Ends Gear Ratio: 5.57
<b>CAB:</b>	Conventional 6-Man Crew Cab
<b>TIRE, FRONT:</b>	(2) 12R22.5 Load Range H XDN2 (MICHELIN), 483 rev/mile, 75 MPH, Drive
<b>TIRE, REAR:</b>	(4) 12R22.5 Load Range H XDN2 (MICHELIN), 483 rev/mile, 75 MPH, Drive
<b>SUSPENSION, REAR, SINGLE:</b>	31,000-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs
<b>PAINT:</b>	Cab schematic 209WK Location 1: 8736, Gray Met (Custom) Location 2: 2484, Red (Custom) Chassis schematic 932WK Wheel: 0001, Canyon Black (Std)

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
Base Chassis, Model HV507 SFA with 201.00 Wheelbase, 82.10 CA, and 75.00 Axle to Frame.	5783/3857	9640

**AXLE CONFIGURATION**

AXLE CONFIGURATION {Navistar} 4x4	174/-97	77
-----------------------------------	---------	----

Notes

: Pricing may change if axle configuration is changed.

**ENGINE**

ENGINE, DIESEL {Cummins L9 380} EPA 2024, 380HP @ 2100 RPM, 1150 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 380 Peak HP (Max), (RATED FOR EMERGENCY VEHICLES ONLY)	560/4	564
EMISSION, CALENDAR YEAR {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2024	0/0	0
CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty	0/0	0
CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations	0/0	0
EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	0/0	0
RADIATOR Aluminum, Cross Flow, Front to Back System, 1228 SqIn, with 1167 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler	23/-5	18

Includes

: DEAERATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

: RADIATOR HOSES Premium, Rubber

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed	0/0	0
---	-----	---

Includes

: FAN Nylon

AIR CLEANER Single Element	0/0	0
ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls and Starter Lockout, with Ignition Switch Control, for Cummins B6.7 and L9 Engines	0/0	0
ENGINE WATER COOLER {Sen-Dure} Auxiliary, For Use with Fire Trucks	17/3	20
FAN OVERRIDE Manual; with Electric Switch on Instrument Panel, (Fan On with Switch On)	0/0	0
THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel	0/0	0

**TRANSMISSION**

TRANSMISSION, AUTOMATIC {Allison 3000 EVS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor	215/68	283
ALLISON SPARE INPUT/OUTPUT for Emergency Vehicle Series (EVS), Fire/Pumper, Tank, Aerial/Ladder, Package Number 198, Includes J1939 Based Auto Neutral	0/0	0
AUTOMATIC NEUTRAL Allison Transmission Shifts to Neutral When Parking Brake is Engaged and Remains in Neutral When Parking Brake is Disengaged, without On/Off Switch	0/0	0
NEUTRAL AT STOP OMIT	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
OIL COOLER, TRANSMISSION {Modine} Water to Oil Type	25/0	25
OIL COOLER, TRANSFER CASE with Oil Coolant Lines Routed to Oil Cooler	6/1	7
PROVISION FOR PTO Top Mount; with Allison 3000 Transmission	0/0	0
PTO LOCATION Dual, Customer Intends to Install PTO at Left and/or Right Side of Transmission	0/0	0
SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming	0/0	0
TRANSFER CASE {Meritor MTC-4210} 2-Speed, 10,000 lb-ft Torque Rating, with PTO Provision, Electric Over Air Control, with Lube Pump	385/403	788
TRANSFER CASE LUBE {EmGard 50W} Synthetic; 1 thru 14.99 Pints	0/0	0
TRANSMISSION DIPSTICK Relocated to Right Side of Transmission	1/0	1
TRANSMISSION OIL Synthetic; 29 thru 42 Pints	0/0	0
TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1

### CLUTCH

CLUTCH Omit Item (Clutch & Control)	0/0	0
-------------------------------------	-----	---

### REAR AXLES, SUSPENSIONS

AXLE, REAR, SINGLE {Dana Spicer S26-190} Single Reduction, 26,000-lb Capacity, R Wheel Ends . Gear Ratio: 5.57	0/338	338
SUSPENSION, REAR, SINGLE 31,000-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs	0/132	132

### FRONT AXLES

AXLE, FRONT DRIVING {Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel Mounting	737/0	737
---	-------	-----

#### Notes

: Axle Lead Time is 90 Days

### FRONT SUSPENSIONS

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers	44/0	44
--	------	----

### CABS, COWLS, BODIES

CAB Conventional 6-Man Crew Cab	347/303	650
ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Crew Cab	44/39	83
AIR CONDITIONER with Integral Heater and Defroster	0/0	0
CAB INTERIOR TRIM Classic, for Crew Cab	0/0	0

#### Includes

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger

: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap		
CAB, INTERIOR TRIM, CLOSEOUT Under IP, Driver Side	0/0	0
CAB REAR SUSPENSION Air Bag Type	0/0	0
CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator	12/0	12
COVER PLATE Blank Steel Cover Plate in Place of Storage Bin for Customer Mounting Requirements	0/0	0
GAUGE CLUSTER Premium Level; English with English Electronic Speedometer	0/0	0
<u>Includes</u>		
: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for		
: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure		
: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)		
GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel	2/0	2
GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission	1/0	1
GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	0/0	0
GAUGE, VOLTMETER Auxiliary Gauge, Located in Center Panel. Standard Cluster Also Includes Digital Voltage Readout	0/0	0
VIRTUAL GAUGE, AIR APPLICATION Requires Premium Cluster	0/0	0
VIRTUAL GA, OIL TEMP,AUTO XMSN for Allison Transmission, Requires Premium Cluster	0/0	0
VIRTUAL GA,OIL TEMP,REAR AXLE Requires Premium Cluster	0/0	0
GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar	6/0	6
GRAB HANDLE, ADDITIONAL EXT (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, Mounted Left and Right Side, Rear of Rear Doors, for Crew Cab	5/0	5
GRAB HANDLE, CAB INTERIOR (4) Safety Yellow, Crew Cab	0/0	0
INSTRUMENT PANEL Flat Panel	0/0	0
IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	0/0	0
<u>Notes</u>		
: Mirror Dimensions are Rounded to the Nearest 0.5"		
MONITOR, TIRE PRESSURE Omit	-9/-2	-11
SEAT BELT All Red; 4 to 6	0/0	0
SEAT, DRIVER {H.O. Bostrom Sierra Air 100} NFPA Compliant, Air Suspension, High Back, Vinyl with Covered Back and International Logo on Headrest, for Fire Truck	10/3	13
SEAT, PASSENGER {H.O. Bostrom Sierra Air 100} NFPA Compliant, Air Suspension, High Back, Vinyl with Covered Back, International Logo on Headrest, for Fire Truck	77/30	107
SEAT, REAR {H.O. Bostrom Tanker 400CT} for SCBA; Two Individual Seats on One Riser, Non Suspension, High Back, Vinyl, with Covered Back and International Logo on Headrest	168/67	235

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
SEATBELT WARNING PREWIRE Includes Seat Belt Switches and Seat Sensors for all Belted Positions in the Cab and a Harness Routed to the Center of the Dash for the Aftermarket Installation of the Data Recorder and Seatbelt Indicator Systems, for 4 to 6 Seat Belts	0/0	0
WINDOW, MANUAL (4) and Manual Door Locks, Front and Rear Doors, Left and Right	0/0	0
<b>FRAMES</b>		
FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.437" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL	192/481	673
BUMPER, FRONT Swept Back, Steel, Painted 0001 Canyon Black, Heavy Duty	0/0	0
FRAME DIMPLE Dimple on Left and Right Top Flange of Frame Rail to Reference Rear Axle Centerline	0/0	0
FRAME EXTENSION, FRONT Integral; 20" In Front of Grille	136/-31	105
TOW HOOK, FRONT (2) Frame Mounted	8/0	8
WHEELBASE RANGE 181" (460cm) Through and Including 205" (520cm)	183/-183	0
<b>BRAKES</b>		
BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	0/0	0
<u>Includes</u>		
: BRAKE LINES Color and Size Coded Nylon		
: DRAIN VALVE Twist-Type		
: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster		
: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel		
: PARKING BRAKE VALVE For Truck		
: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4		
: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6		
AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control	6/2	8
BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	1/0	1
BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity	-23/0	-23
BRAKE CHAMBERS, FRONT AXLE {MGM} 20 Sqli	-1/0	-1
SLACK ADJUSTERS, FRONT {Haldex} Automatic	14/0	14
DUST SHIELDS, FRONT BRAKE for Air Cam Brakes	10/0	10
BRAKES, REAR {Meritor 16.5X7 Q-PLUS HD} Air S-Cam Type, Cast Spider, Heavy Duty Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 26,000-lb Capacity per Axle	0/85	85
BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/36 Sqli Spring Brake	0/23	23
SLACK ADJUSTERS, REAR {Haldex} Automatic	0/16	16
DUST SHIELDS, REAR BRAKE for Air Cam Brakes	0/10	10
BRAKE CHAMBERS, POSITION Rotated Forward and Up For Maximum Ground Clearance with 4x4	0/0	0
AIR COMPRESSOR {Cummins} 18.7 CFM	0/0	0
AIR DRYER {Bendix AD-IP} with Heater	13/14	27
AIR DRYER LOCATION Mounted Inside Left Rail, Behind Transfer Case Mounting	5/5	10

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
AIR TANK LOCATION (2) Mounted Left Side BOC Under Battery Box	-9/19	10
DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank	2/0	2
<b>STEERING</b>		
STEERING GEAR {Sheppard M110} Power	43/-2	41
STEERING COLUMN Tilting	13/2	15
STEERING WHEEL 4-Spoke; 18" Dia., Black	0/0	0
<b>DRIVELINES</b>		
DRIVELINE SYSTEM {Dana Spicer} SPL170 Main Driveline, 1710 Driveline to Transfer Case, SPL140 Driveline to Front Axle, for 4x4	7/31	38
<b>EXHAUST SYSTEMS</b>		
EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab, for All-Wheel Drive	57/-1	56
AFTERTREATMENT COVER Steel, Black	11/2	13
ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger	0/0	0
SWITCH, FOR EXHAUST 3 Position, Momentary, Lighted Momentary, ON/CANCEL, Center Stable, INHIBIT REGEN, Mounted in IP Inhibits Diesel Particulate Filter Regeneration When Switch is Moved to ON While Engine is Running, Resets When Ignition is Turned OFF	2/0	2
<b>ELECTRICAL SYSTEMS</b>		
ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
<u>Includes</u>		
: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab		
: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel		
: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever		
: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light		
: STARTER SWITCH Electric, Key Operated		
: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector		
: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature		
: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever		
: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted		
: WIRING, CHASSIS Color Coded and Continuously Numbered		
ALTERNATOR {Leece-Neville BLP4006HN} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote Sense	17/0	17
ANTENNA for Increased Roof Clearance Applications	1/0	1
BATTERY BOX Steel, with Plastic Cover, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Fuel Tank	-19/19	0
BATTERY DISCONNECT SWITCH for Cab Power Disconnect Switch, Disconnects Power to Power Distribution Center (PDC) and Body Builder Through Solenoid, Does Not Disconnect Charging Circuits, Locks with Padlock, Cab Mounted	11/2	13
BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud	28/25	53

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
BODY BUILDER WIRING To Rear of Frame, with Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket	2/0	2
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
CIGAR LIGHTER Includes Ash Cup	1/0	1
CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	0/0	0
COURTESY LIGHT (4) Mounted In Front & Rear Map Pocket Left and Right Side	2/0	2
DATA RECORDER Includes Display Mounted in Overhead Console	2/0	2
HEADLIGHTS Halogen, with Daytime Running Lights	0/0	0
HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord	3/0	3
HORN, ELECTRIC (2) Disc Style	1/0	1
IGNITION SWITCH Keyless	2/0	2
INDICATOR, BATTERY WARNING Green BATTERY ON Indicator, Mounted on Left Side of Instrument Panel, To be Used with Factory Installed or Customer Mounted Battery Disconnect Switch	1/0	1
INDICATOR, LOW COOLANT LEVEL with Audible Alarm	0/0	0
POWER SOURCE Cigar Type Receptacle without Plug and Cord	1/0	1
POWER SOURCE, ADDITIONAL Two Auxiliary Power Outlets (APO) with Two USB-A Ports and Two USB-C Ports, Located in the Instrument Panel	0/0	0
RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	3/0	3
RADIO, AUXILIARY CONTROLS Mounted in Steering Wheel, Radio Function Control Switch, Includes Volume Up/Down, Mute, Forward/Back and Bluetooth Answer/Disconnect	8/2	10
SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars	6/2	8
STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt, Less Thermal Over-Crank Protection	8/1	9
SWITCH, AIR HORN, PASSENGER Fire Truck Application; Momentary Switch Located in Instrument Panel Close to Passenger, Driver Also To Activate Switch with Lanyard	0/0	0
TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender	0/0	0
WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0
WIRING MODIFICATIONS for J1939, with 8' of J1939 250K Body Bus Wiring Coiled Inside Left Rail Behind Transmission, Data High to Pin A, Data Low to Pin B, to Communicate with Pressure Governor	1/0	1
<b>FRONT END</b>		
FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV	0/0	0
FENDER EXTENSIONS Rubber	6/0	6
GRILLE Stationary, Painted Grille & Headlight Bezels 8752 Charcoal Metallic	0/0	0
GRILLE EMBER SCREEN Mounted to Grille and Cowl Tray to Keep Hot Embers out of Engine and HVAC Air Intake System	3/0	3
LOGOS EXTERIOR Model Badges	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
LOGOS EXTERIOR, ENGINE Badges	0/0	0
<b><u>SPEEDOMETER, TOOLS, MISC</u></b>		
COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360	1/0	1
KEYS - ALL ALIKE, ID I-1003 Compatible with Z-001	0/0	0
PAINT IDENTITY, PT-2 Single Color, Instruction No. 932. Wheels	0/0	0
PAINT SCHEMATIC, PT-1 Two Tone, Design 209.	0/0	0
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
PAINT CLASS Single Custom Color	0/0	0
<b><u>FUEL TANKS</u></b>		
FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab	25/4	29
DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab	0/0	0
FUEL COOLER Less Thermostat; Mounted in Front of Cooling Module	14/0	14
FUEL/WATER SEPARATOR {Racor 400 Series} with Primer Pump, Includes Water-in-Fuel Sensor, Mounted on Engine	0/0	0
<b><u>WHEELS, TIRES - FRONT</u></b>		
WHEELS, FRONT {Accuride 28828} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and with Steel Hubs	14/0	14
(2) TIRE, FRONT 12R22.5 Load Range H XDN2 (MICHELIN), 483 rev/mile, 75 MPH, Drive	34/0	34
<b><u>WHEELS, TIRES - REAR</u></b>		
WHEELS, REAR {Accuride 28828} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and with Steel Hubs	0/28	28
(4) TIRE, REAR 12R22.5 Load Range H XDN2 (MICHELIN), 483 rev/mile, 75 MPH, Drive	0/68	68
<b><u>BODY INTEGRATION</u></b>		
BDY INTG, I/O EXP HARNESS {for Diamond Logic Builder} In-Cab wire harness (DLB) program only, Includes a harness with five blunt cut wires routed on lower left of instrument panel. Two ground active inputs and two (.5Amp) relay drivers outputs are provided	0/0	0
<b>Services Section:</b>		
<b><u>WARRANTY</u></b>		
WARRANTY Standard for HV507, HV50B, HV607 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A	0/0	0
<b>Total Component Weight:</b>	<b>9480/5768</b> (lbs)	<b>15248</b> (lbs)
	(lbs)	(lbs)

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

# Short Spec

North-West Fire Protection District  
 Milan Horak  
 21455 US HWY 285  
 Fairplay, CO 80440  
 719-427-0002  
 mhorak@nwfpd.org

North-West Fire Protection District  
 Milan Horak  
 21455 US HWY 285  
 Fairplay, CO 80440  
 719-427-0002  
 mhorak@nwfpd.org

<b>Exp. Date:</b>	05/13/2023	
<b>Quote No:</b>	10064-0006	
<b>BID PREP:</b>	G0-09-0020	EXT Timberwolf Bid Prep Forms
<b>WARRANTY:</b>	G0-09-2020	EXT Timberwolf Warranties-BR
<b>ELEC-DC:</b>	G0-50-1000	EXT Timberwolf - DC Elec System
<b>CHS MODS:</b>	G0-10-0100	EXT Timberwolf SA Chassis Modifictns
<b>PLUMBING:</b>	G0-20-2100	EXT Timberwolf Pump&Plumbing
<b>PUMP COMPT:</b>	G0-26-2100	EXT Timberwolf Pump Cmpt
<b>BODY-PMPR:</b>	G0-30-3700	EXT Timberwolf 1000 Gal Long Body
<b>BODY-CMMN:</b>	G0-44-0100	EXT Timberwolf Common Body Parts
<b>ELEC-AC:</b>	G0-60-1000	EXT Timberwlf - AC Electrical System
<b>EQUIP-SYST:</b>	G0-70-1000	EXT Timberwolf - Equipment Systems
<b>PAINT:</b>	G0-80-1000	EXT SA Timberwolf - Pnt/Ltr/Str
<b>EQUIP-LSE:</b>	G0-90-0000	EXT Pmpr/Tnkr - Loose Equipment

06/15/2023

Page 1

PART NO	DESCRIPTION	QTY
00-00-1100	Information Request Form (Factory Required)	1
00-00-1200	Chassis Information Summary (Factory Required)	1
00-00-1300	North-West Fire Protection District	1
00-00-1499	Overall Height Restriction, NONE	1
00-00-1509	Overall Length Restriction, NONE	1
00-00-1519	Overall Width Restriction, NONE	1
00-00-1529	Wheelbase Restriction, NONE	1
<b>NFPA Equipment Allowances</b>		
00-00-1610	NFPA Pumper Equipment Allowance 2500#	1
00-00-3220	Contract Change Notice	1
00-12-1100	Financial Stability Response	1
01-06-0590	Performance Testing, Tilt Angle, Not Req'd, Comparable BUILD	1
01-16-0150	-- Warranty, Apparatus, Body Warranty, 1 Year	1
01-19-0460	-- Warranty, Body, Alum, Life-Time, Transferable	1
01-19-2450	-- Warranty, Subframe, Lifetime Alum, Transferable	1
01-20-1012	-- Warranty, Paint, AkzoNobel, 10 Year EXT	1
01-21-0150	-- Warranty, Lettering and Striping, 1 Year	1
01-17-0870	-- Pump Warranty, Rosenbauer, 5 Year	1
02-14-6250	Plumbing Warranty, Stainless Steel SST, 10 Years	1
01-33-3100	-- Manuals, Body Complete, 1 Set Printed	1
02-90-1500	Chassis, International 4 Dr	1
50-09-3105	Elecal, Base, Rosenbauer LCS 2.0 - Tmbrwlf/Airwlf	1
55-11-1301	-- Dr Open/Hazard Wrm Lt, Flashing LED, Red, Clear Lens, Whelen TIR3	1
50-12-1560	Electrical Console, In Cab, Rosenbauer LCS 2.0, Tmbrwlf/Arwlf, International	1
50-15-1100	Batteries, With Supl'd Chs	1
50-15-3100	Battery Swtch, Mstr Disconnect , Chs Sppld	1
50-15-3410	Ignition Swtch, Keyless, w/Chassis	1
50-15-5785	Battery Charger, KUSSMAUL, Chief Series 6012	1
50-16-1100	-- Display, Bar Graph, Sngl Battery Bank 091-199-001	1
50-20-1124	Shore Power Inlet, Below Left Front Cab Door, Commercial	1
50-20-1500	Shore Power Inlet, KUSS Super Auto-Eject 20A	1
50-41-7100	Air Horns (2) 24" Round Hadley E-Tone	1
50-41-8180	Air Horn Location Hood Mounted, 1 Ea Side	1
50-43-1000	Air Horn Cntrls	1

PART NO	DESCRIPTION	QTY
50-43-2000	-- Air Horn Cntrl, Driver, Horn Ring, Air/Elec	1
50-43-2200	-- Air Horn Cntrl, Officer, Sgle Ft Swtch	1
51-05-6200	Lt, Engine Cmpt, 12 Volt LED, w/Swtch	1
51-05-9000	-- Switch on Light Head	1
51-20-3110	Fldlt, Mntg Lctn, Front Edge Of Cab Roof, Tmbrwlf/Airwlf	2
51-15-4164	-- Fldlt, Fire Research, Evolution FCA812-V20-02, Contour Brow Mount, IH7400	2
54-15-6002	-- Scene Lt Swtch , Front Scene Lts, Cab Switch Panel	1
52-01-1210	Back Up Alarm, EXT	1
52-02-1150	Back Up Camera, ASA, Color	1
52-08-1009	-- Hand Lights, NFPA Compliance - Spl'd/Inst'l'd by DEPT	1
52-41-1400	Seat Belt Warning/VDR System, Weldon/Akron	1
53-01-1201	Marker Lts, LED, DOT Requirements, Tmbrwlf/Airwlf	1
53-02-1250	License Plate Brkt, Cast Prdts, LP0005-1-C w/ LED Lt	1
53-03-0065	Whelen Rr DOT LED Ltng Pkg M6	1
53-03-2750	-- Tail/Brake Lts, Whelen, LED, M62BTT (Pair)	1
53-04-2750	-- Turn Signals, Whelen, LED w/ Arrow, M62T (Pair)	1
53-06-3550	-- Backup Lts, Whelen, LED, M62BU (Pair)	1
53-07-1210	-- Tail Lt Bezel, 4 Lts, Whln M6 (Pair), ABS Chrome	1
53-05-1800	Turn Signals, Mid Bdy, LED Marker Lt (Pair)	1
54-02-1520	-- Ground Lts, Cab, 4-Dr, LED, Whelen 3SC0CDCR Four	1
54-03-1420	-- Ground Lts, Mid Body, LED, Whelen 3SC0CDCR, Pair	1
54-03-1620	-- Ground Lts, Rr Step, LED, Whelen 3SC0CDCR, Pair	1
54-03-1820	-- Ground Lts, Bhnd Rr Wheels, LED, Whelen 3SC0CDCR, Pair	1
54-04-1999	-- Lt Swtch , Ground Lts w/ Park Brake	1
54-10-1300	Step Lt, Fxd /Fldg Step, LED, Ea	3
54-11-2100	Lt Swtch , Step/Wlkwy Lts Wired Park Brake Swtch	1
54-15-4600	Scene Lt, Fire Research, Spectra, LED SPA260-Q15, Chrm, Surface Mount	4
54-15-5500	-- Scene Lt Lctn, Left Side Of Bdy	2
54-15-5600	-- Scene Lt Lctn, Right Side Of Bdy	2
54-15-6470	-- 3-Way Cntrl Swtch, Left Scene Lts, Cab Dash/Pmp Pnl	1
54-15-6570	-- 3-Way Cntrl Swtch, Right Scene Lts, Cab Dash/Pmp Pnl	1
54-15-4510	Scene Lt, Fire Research, LED SPA900-Q70, Surface Mount	2
54-15-5700	-- Scene Lt Lctn, Rr Of Bdy	2
54-15-6670	-- 3-Way Cntrl Swtch, Rr Scene Lts, Cab Dash/Pmp Pnl	1
54-15-6700	-- Scene Lt Swtch , Rr Scene Lts, Auto w/ Reverse	1
56-01-1600	Siren, Elect, Whelen 295SLSA1	1
56-02-1600	-- Spkr, F-S Dynamax, ES100C 100 Watt	1
56-02-1650	-- Spkr Grille, SST, "R"	1
56-03-1800	-- Spkr Lctn, To Be Determined by Body Mfg	1
57-02-1900	-- Lt Bar, Whelen, Justice, LED, 56" JE2NFPA	1
57-10-0100	-- Lightbar Cntrl, with Vista E-Master & Virtual Switch	1
58-71-1770	-- Wrn Lts, Whelen, Upper Rr (2) M9 LED	1
57-20-1400	-- Wrn Lt, Drvr, Whelen, M9, Red LED, Color Lens, Ea	1
57-20-1403	-- Wrn Lt, Offcr, Whelen, M9, Blue LED, Color Lens, Ea	1
58-01-2180	-- Flange, Chrome, Wrn Lt, Whln, M9 Ea	2
58-61-2100	-- Wrn Lts, Whelen, Upper Side Rr (2) M9 LED	1
57-20-1400	-- Wrn Lt, Drvr, Whelen, M9, Red LED, Color Lens, Ea	1
57-20-1403	-- Wrn Lt, Offcr, Whelen, M9, Blue LED, Color Lens, Ea	1
58-01-2180	-- Flange, Chrome, Wrn Lt, Whln, M9 Ea	2
58-03-2000	-- Wrn Lts, Whelen, Low Frnt, (2) M6 LED	1
57-20-1200	-- Wrn Lt, Drvr, Whelen, M6, Red LED, Color Lens, Ea	1
57-20-1203	-- Wrn Lt, Offcr, Whelen, M6, Blue LED, Color Lens, Ea	1
58-01-2140	-- Flange, Chrome, Wrn Lt, Whln, M6, Ea	2
58-09-2000	-- Wrn Lts, Whelen, Intrsct (2) M6 LED	1
57-20-1200	-- Wrn Lt, Drvr, Whelen, M6, Red LED, Color Lens, Ea	1
57-20-1203	-- Wrn Lt, Offcr, Whelen, M6, Blue LED, Color Lens, Ea	1
58-01-2140	-- Flange, Chrome, Wrn Lt, Whln, M6, Ea	2
58-36-2000	-- Wrn Lts, Whelen, Low Rr Side (2) M6 LED	1
57-20-1200	-- Wrn Lt, Drvr, Whelen, M6, Red LED, Color Lens, Ea	1
57-20-1203	-- Wrn Lt, Offcr, Whelen, M6, Blue LED, Color Lens, Ea	1
58-01-2140	-- Flange, Chrome, Wrn Lt, Whln, M6, Ea	2
58-81-2000	-- Wrn Lts, Whelen, Low Rr (2) M6 LED	1
57-20-1200	-- Wrn Lt, Drvr, Whelen, M6, Red LED, Color Lens, Ea	1
57-20-1203	-- Wrn Lt, Offcr, Whelen, M6, Blue LED, Color Lens, Ea	1
10-01-1100	Vehicle Dimensions, Single Axle	1

PART NO	DESCRIPTION	QTY
10-02-1100	Label, Data, Fluid Levels	1
10-02-1200	Label, Data, Height x Length, Weight	1
10-02-1300	Label, Data, "No Ride" Rr Step	1
10-02-1400	Label, Data, Tire Pressure	1
10-02-2100	Label, Indicating Number of Seats	1
10-02-2500	Label, "Caution: Do Not Wear Helmet While Seated"	1
10-03-1230	Chassis Preparation, Comm, 4 Door, Tmbrwlf/Airwlf	1
10-03-6500	Tow Plates (2), Rear Frame Rail, Under Rear Body, Tmbrwlf/Airwlf	1
80-43-2400	-- Painting, Tow Plates, Blk	1
10-04-2154	Bumper Extension, 20", By Body Builder	1
10-04-2344	-- Bumper Gravelshield, 20", By Body Builder	1
10-04-3570	Bumper, Flat Style, Polished SST Cladding, Tmbrwlf	1
10-04-2600	-- Battery Compartment, Driver Bumper, Timberwolf/Airwolf	1
10-04-2930	-- Battery Compartment, Passenger Bumper, Timberwolf/Airwolf	1
10-18-4000	-- Batteries, Relocate Chassis Supplied, L1/R1 Compartment	1
10-18-1200	-- Battery Jump Start Lugs, Studs and Caps, Near Driver's Door	1
10-06-1600	Tire Pressure Indicator, Single Axle, Commercial, RWTG1235	1
10-07-2110	Exhaust, Vertical, With Chassis, Navistar	1
10-07-3410	Exhaust Tip, Angled, Chrome, 4" O.D.	1
10-08-2100	Mud Flaps, Rear Wheels, Black, w/ Body	1
10-10-0800	Cab Step Overlay, 4 Door Driver Side w/Compartment	1
10-10-0900	Cab Step Overlay, 4 Door Passenger Side w/Compartment	1
10-12-6300	SCBA Bracket, Cab Seat, Zico "NFPA" Restraint, Ea HZ-KD-ULLH	5
10-19-2100	Air Brake Cmprsr, KUSS, 120V, #091-9B-1	1
20-27-1111	-- Pump, Rosenbauer, NH55-1250 GPM, NPHP, PTO, LCS - Tmbrwlf	1
20-27-6210	-- Primer, Rosenbauer, Automatic, LCS Belt driven	1
20-28-3410	-- Pump Shift, Rosenbauer, PTO, Pump and Roll, Tmbrwlf/Airwlf	1
20-28-4015	-- Supply Valve, High Pressure, Elec, LCS	1
21-00-3350	-- Piping, SST - 1250 GPM & Up *	1
21-01-5600	-- Intk Manifold, SST	1
21-01-6600	-- Dschg Manifold, SST	1
21-01-7300	-- Painting, Pump & Piping, Unpainted	1
21-01-8100	-- Threads, National Hose (NST)	1
22-30-4110	-- Intk, Mstr, Gtd, 6", Mnl, Bttrfly, Rr Ctr - Tmbrwlf	1
21-01-2300	-- Drain/Bleeder, Class 1, Mnl 1/4 Turn	1
22-41-5700	-- Cap, 6", Chrome Long Hndl	1
22-51-8812	-- Tank-To-Pump, Water Tank, 4" Butterfly Vlv, N/NH1250, One LCS, EXT	1
23-02-1211	-- Tank Fill/Cooling Line, Water Tank, 1-1/2", One LCS, Tmbrwlf/Airwlf	1
25-08-2220	-- Foam Capability, HP-FIXMIX & NP FRC Turbo Foam - Tmbrwlf	1
25-08-1221	-- Foam System, RBA, HP-FIXMIX, LCS - Tmbrwlf	1
25-08-1310	-- HP-FIXMIX, Foam Supply	1
25-08-1332	-- Proportioning Rate, HP-FIXMIX, 1%	1
25-20-1090	-- Foam Plmbg, HP-FIXMIX, Class A	1
25-09-6100	-- Foam System, FRC TurboFoam TFC100	1
25-09-6500	-- FRC TurboFoam Capabilities: 1.6GPM @ 400PSI	1
25-09-6872	-- Check Valve, Foam Tank 1", TFC100/200/300/400	1
25-09-6916	-- Discharge Check Valve Assembly 3" w/Sensor Mount	1
25-09-6950	-- Tank Float Switch, Side Mount	1
25-20-1500	-- Foam Plmbg, Sngl Class A Tank, 1" Mnl Vlv - Tmbrwlf	1
25-21-1510	-- Foam Tank, Intgrl Poly, 30 Gal, Class A - Tmbrwlf	1
25-22-9100	-- Foam Tank, No Manufacturer Preference	1
25-23-1002	-- Foam Tank Drain, Cls 1" Ball Vlv, Under Tank	1
27-10-5020	-- Pressure Gvrnr, Rosenbauer, Tmbrwlf LCS 2.0	1
27-01-3310	-- Mstr Gauges, Rosenbauer, LCS 2.0, Digital, Pres/Vacuum	1
27-01-4100	-- Gauge, Test Taps	1
27-03-1600	-- Gauge, Dschg, 2-1/2" 600#, High Pressure Pumps, Mntd on pump Panel	1
27-03-1800	-- Gauge, Dschg, Digital, In Cab, Pump and Roll	1
27-35-3000	-- Water Level Display, DigiView, Pump Panel, LCS 2.0, Tmbrwlf	1
27-35-3200	-- Water Level Display, DigiView, In-Cab, LCS 2.0, Tmbrwlf	1
27-36-3000	-- Foam Tank Gauge, DigiView, Class A, Pump Panel, LCS 2.0, Tmbrwlf	1
27-36-3300	-- Foam Tank Gauge, DigiView, Class A, In-Cab, LCS 2.0, Tmbrwlf	1
20-30-3400	-- Pump Instln, Rr Mt PTO, By Bdy Bldr	1
20-31-1000	Fire Pump Testing - Pumpers/Tankers	1
20-31-1100	-- Pump Test, Pumper, UL	1
20-31-1500	-- Pump Test, Label	1

PART NO	DESCRIPTION	QTY
20-31-3200	Dump-Relief Vlv, Suction Side, ELK #40, NST	1
20-31-4110	Pump Cooler, Bypass-To-Tank, 3/8", IC Mini-Twist Handle	1
20-31-4700	Pump Cooler, Rosenbauer, Thermal	1
20-31-5204	Heat Exchanger, Engine, Complete, IC Mini-Twist Handle	1
22-30-1110	Intk, Gtd, 2-1/2" NST, Left Rear, Rr Mt - Tmbrwlf/Airwlf	1
21-01-2302	-- Drain/Bleeder, Class 1, Mnl 1/4 Turn - Spec Only	1
22-41-1100	-- Plug, 2-1/2", Chrome Rocker Lug, w/Chain	1
24-62-1258	-- Vlv Mfgr, AKR, 8000, (2-1/2"), Mnl Swg Cntrl Only	1
22-55-4050	-- Intk Vlv Cntrl, AKR, Mnl Swing Type-Adjacent	1
23-14-9120	Pkg, Bumper Monitor & (1) Front Bumper Crosslay, Tmbrwlf	1
23-14-2510	-- Dschg, 1-1/2", Front RH Bumper Monitor, Tmbrwlf	1
23-14-2560	-- Dschg, 1-1/2", Front Bumper Monitor, Plumbed High Pressure	1
24-15-3520	-- Mntr, ELK, Frnt Bmpr, EXM2HD Package, #71X2NH6CIM	1
23-14-3110	-- Dschg, 1-1/2" Frnt Bmpr Crosslay, Tmbrwlf/Airwlf	1
10-04-2560	-- Bumper Crosslay Hosebed, Full Width, (1) 150' 1-3/4", Timberwolf	1
23-16-2900	-- Crosslay/Speedlay, Equipment Securement, NFPA	1
23-16-3300	-- Crosslay Cover, Vinyl, Top and Sides	1
29-20-5600	-- Vinyl Cover, Color, RED	1
24-61-1202	-- Vlv Mfgr, AKR, 8000, (2"), Mnl Swng Type-Adj, Lckg	1
24-53-0800	-- Dschg Vlv Cntrl, AKR, Mnl Swing Type-Adjacent, Lckg	1
27-02-1500	-- Gauge, Dschg, IC, 2-1/2" (0-400 PSI), WF	1
21-01-2202	-- Drain/Bleeder, Class 1, Automatic - Spec Only	1
23-20-2110	Dschg, 2-1/2", Rr Cntr Pmp Pnl, Left Side, Tmbrwlf/Airwlf	1
21-01-2302	-- Drain/Bleeder, Class 1, Mnl 1/4 Turn - Spec Only	1
24-02-1202	-- Elbow, Flange x 2-1/2"M, Chrome	1
24-03-1400	-- Cap, 2-1/2", NST Chrome, Rocker Lug, w/Chain	1
24-61-1252	-- Vlv Mfgr, AKR 8000, 2-1/2", Mnl Swng Type-Adj, TS-7	1
24-53-0820	-- Dschg Vlv Cntrl, AKR, Mnl Swing Type-Adj, TS-7	1
27-02-1500	-- Gauge, Dschg, IC, 2-1/2" (0-400 PSI), WF	1
23-20-2310	Dschg, 2-1/2", Rr Cntr Pmp Pnl, Right Side, Tmbrwlf/Airwlf	1
21-01-2302	-- Drain/Bleeder, Class 1, Mnl 1/4 Turn - Spec Only	1
24-02-1202	-- Elbow, Flange x 2-1/2"M, Chrome	1
24-03-1400	-- Cap, 2-1/2", NST Chrome, Rocker Lug, w/Chain	1
24-61-1252	-- Vlv Mfgr, AKR 8000, 2-1/2", Mnl Swng Type-Adj, TS-7	1
24-53-0820	-- Dschg Vlv Cntrl, AKR, Mnl Swing Type-Adj, TS-7	1
27-02-1500	-- Gauge, Dschg, IC, 2-1/2" (0-400 PSI), WF	1
23-20-2610	Dschg, 2-1/2", Left Rear Upper Face, Tmbrwlf/Airwlf	1
21-01-2302	-- Drain/Bleeder, Class 1, Mnl 1/4 Turn - Spec Only	1
24-01-2400	-- Adptr, Reducing, 2-1/2" NST F x 1-1/2" NST M, Chrome	1
24-03-1200	-- Cap, 1-1/2", NST Chrome, Rocker Lug, w/Chain	1
24-61-1252	-- Vlv Mfgr, AKR 8000, 2-1/2", Mnl Swng Type-Adj, TS-7	1
24-53-0820	-- Dschg Vlv Cntrl, AKR, Mnl Swing Type-Adj, TS-7	1
27-02-1500	-- Gauge, Dschg, IC, 2-1/2" (0-400 PSI), WF	1
23-20-2910	Dschg, 2-1/2", Right Rear Upper Face, Tmbrwlf/Airwlf	1
21-01-2302	-- Drain/Bleeder, Class 1, Mnl 1/4 Turn - Spec Only	1
24-01-2400	-- Adptr, Reducing, 2-1/2" NST F x 1-1/2" NST M, Chrome	1
24-03-1200	-- Cap, 1-1/2", NST Chrome, Rocker Lug, w/Chain	1
24-61-1252	-- Vlv Mfgr, AKR 8000, 2-1/2", Mnl Swng Type-Adj, TS-7	1
24-53-0820	-- Dschg Vlv Cntrl, AKR, Mnl Swing Type-Adj, TS-7	1
27-02-1500	-- Gauge, Dschg, IC, 2-1/2" (0-400 PSI), WF	1
24-30-3310	-- Hose Reel, HAN, LH Under Cab Cmpt, Elec, Stl Pntd - Tmbrwlf	1
10-04-2600	-- Battery Compartment, Driver Bumper, Timberwolf/Airwolf	1
10-04-2930	-- Battery Compartment, Passenger Bumper, Timberwolf/Airwolf	1
24-31-2100	-- Hose Reel, Rwnd Cntrl, Weatherproof Push Button	1
24-32-1210	-- Dschg, Hose Reel, 1", Class 1 Valve	1
24-32-1800	-- Dschg, Hose Reel, Plmbd to High Pressure	1
24-33-1300	-- Hose, Water, 800#, 3/4-in x 150-ft, Three (3) 50-ft Lengths	1
24-33-7200	-- Nzl, Rosenbauer, Servo-Nepiro, High Pres, 1" NST	1
24-33-8000	-- Nzl, Mtg, Hose Reel	1
24-33-9600	-- Roller, Hose Reel, Captive, Four Sided	1
24-30-3410	-- Hose Reel, HAN, RH Under Cab Cmpt, Elec, Stl Pntd - Tmbrwlf	1
24-31-2100	-- Hose Reel, Rwnd Cntrl, Weatherproof Push Button	1
24-32-1210	-- Dschg, Hose Reel, 1", Class 1 Valve	1
24-32-1800	-- Dschg, Hose Reel, Plmbd to High Pressure	1
24-33-1200	-- Hose, Water, 800#, 3/4-in x 100-ft	1

PART NO	DESCRIPTION	QTY
24-33-7200	-- Nzl, Rosenbauer, Servo-Nepiro, High Pres, 1" NST	1
24-33-8000	-- Nzl, Mtg, Hose Reel	1
24-33-9600	-- Roller, Hose Reel, Captive, Four Sided	1
80-43-1600	-- Painting, Hose Reel, Silver Grey	2
26-40-1600	Pump Enclsr, Specs, Tmbrwlf/Airwlf	1
26-40-2500	Pump Panel Lctn, TimberWolf, Rr Center	1
26-40-4100	-- Pump Cntrl Panel Enc Door, Rr Mt, Rr Center, Roll Up	1
26-56-1462	-- Pump Panel Lts (2), Rr Mt, (2) Grote #01-61F8-70 Low Profile, LED, Tmbrwlf	1
26-40-3110	Pump Cntrl Panel, Rr Mt SST, Tmbrwlf	1
26-40-5500	Pump Access Panels, Rr Mt, Side Cmpts Bhnd Rr Whls	1
26-55-1100	Labels, Test Data and Safety Placards	1
26-55-2410	Labels, IC Color Coded, EXT	1
27-37-3010	Air Blow Out, Tmbrwlf/Airwlf	1
25-28-1382	Water Tank, 1000 Gal, Poly, T-Tank, Tmbrwlf	1
25-42-1100	-- Water Tank, Base Specs, Poly	1
25-42-1200	-- Water Tank, Manufacturer, UPF, Poly	1
25-44-1700	-- Water Tank, Fill Tower, 10" x 10", EXT	1
25-50-1400	-- Water Tank Clean-out & Plug, 3"	1
29-00-2400	Hosebed, Pmpr, <168" L, HD, 71" Wide - EXT	1
29-10-1050	Hosebed, Grating, Extrd Alum, <168" Long - EXT	1
29-10-5020	Hosebed Storage Cpcty, EXT	1
29-10-5090	-- Hosebed, Strge Cpcty, 30 Cubic Feet, Minimum	1
29-10-8150	Hosebed, Divider, 1/4" Alum, EXT	1
29-10-8300	-- Hosebed, Divider, Handhole Cutouts	1
29-10-8550	Hosebed, Partition, Front of Hosebed, Greater than 48" - EXT	1
29-20-3550	Hosebed Cvr, Alum T/P, <168" L, 49-74" Wide - EXT	1
29-10-8160	-- (1) Main Hosebed Divider (Stationary)	1
29-20-6650	-- Mnl Operation, Hosebed Cvr, Alum T/P	1
29-20-7325	-- Hsbd Cvr Lt, OSS Access, 36" LED Tube Lt, Ea	1
29-20-7800	-- Rr Vinyl Flaps for Alum Cvr	1
29-20-5600	-- Vinyl Cover, Color, RED	1
30-00-0299	Raw Material Surcharge - Single Axle	1
30-01-2040	Bdy Const - Rosenbauer EXT - SA Timberwolf	1
30-01-2250	-- Electrolysis Corrosion Cntrl	1
30-02-1920	-- Side Body Header, Alum, Pntd, Sngl Axle, EXT	1
44-05-1200	-- Whl Well Panel, Alum, Pntd, Sngl Axle	1
44-06-4320	-- Fenderette, Polished Stainless Steel SST, EXT	1
30-10-1510	-- Sub-Frame, EXT, SA Tmbrwlf	1
31-01-7010	100" OAW, Half Dpth Ahd Rr Whls & Ovrwhls, Tmbrwlf	1
31-01-7324	Roll Up Drs, Outside Cmpt, Tmbrwlf, 160" Bdy	1
30-02-1600	-- Drs, Roll-Up, Outside Cmpt, Specs, EXT	1
30-02-1260	-- Dr Strap, EZ-Pull Down, Ea	7
30-02-1750	-- Drs, Safe Step, Specs, EXT (Ea)	4
30-02-1785	-- Finish, Safe Step, Mirror SST, Specs, EXT (Ea)	4
31-01-7300	-- Bdy, Rosenbauer EXT, Timberwolf, 160"	1
32-05-4079	-- Cmpt Height, 79" High Left, High Side, RU Drs	1
32-05-6260	-- Ahd Rr Whls-44" Full Ht Cmpt-Roll Up Outside Cmpt	1
44-40-1020	-- Vents, Compts, Louvers (Ea)	2
55-01-3625	-- RBA InVisiLight, 56" Rcsd, ShvIng, Sides (2) Ea Cmpt, EXT	1
55-06-1100	-- Cmpt Lt, Dr Swtch, Auto, Ea	1
32-05-7042	-- Abv Rr Whls-52" Sngl Cmpt, No Hyd Rack-RU Outside Cmpt	1
44-40-1020	-- Vents, Compts, Louvers (Ea)	2
55-01-3610	-- RBA InVisiLight, 28" Rcsd, ShvIng, Sides (2) Ea Cmpt, EXT	1
55-01-3675	-- RBA InVisiLight, 39" Rcsd, Ceiling Lt, Ea Cmpt, EXT	1
55-06-1100	-- Cmpt Lt, Dr Swtch, Auto, Ea	1
32-05-8460	-- Bhd Rr Whls-48" Full Ht Cmpt-Roll Up Outside Cmpt	1
44-40-1020	-- Vents, Compts, Louvers (Ea)	2
55-01-3620	-- RBA InVisiLight, 45" Rcsd, ShvIng, Sides (2) Ea Cmpt, EXT	1
55-06-1100	-- Cmpt Lt, Dr Swtch, Auto, Ea	1
32-06-4079	-- Cmpt Height, 79" High Right, High Side, RU Drs	1
32-06-6260	-- Ahd Rr Whls-44" Full Ht Cmpt-Roll Up Outside Cmpt	1
44-40-1020	-- Vents, Compts, Louvers (Ea)	2
55-01-3625	-- RBA InVisiLight, 56" Rcsd, ShvIng, Sides (2) Ea Cmpt, EXT	1
55-06-1100	-- Cmpt Lt, Dr Swtch, Auto, Ea	1
32-06-7022	-- Abv Rr Whls-32" Sngl Cmpt w/ Hyd Rack-RU Outside Cmpt	1

PART NO	DESCRIPTION	QTY
44-40-1020	-- Vents, Cmpts, Louvers (Ea)	2
55-01-3610	-- RBA InVisiLight, 28" Rcsd, Shvng, Sides (2) Ea Cmpt, EXT	1
55-06-1100	-- Cmpt Lt, Dr Swtch, Auto, Ea	1
32-06-8460	-- Bhd Rr Whls-48" Full Ht Cmpt-Roll Up Outside Cmpt	1
44-40-1020	-- Vents, Cmpts, Louvers (Ea)	2
55-01-3620	-- RBA InVisiLight, 45" Rcsd, Shvng, Sides (2) Ea Cmpt, EXT	1
55-06-1100	-- Cmpt Lt, Dr Swtch, Auto, Ea	1
33-60-2610	Rr Bdy, 24 Degree Departure Angle, Tmbrwlf/Airwlf	1
32-08-5202	-- Rr Center Cmpt - Full Height/Non Trans - Timberwolf / Airwolf	1
<b>COMPARTMENT STORAGE PROVISIONS</b>		
44-30-1850	-- Roof Access Ladder, Alum Tubing, Fold-Up, Left Rr	1
44-35-2200	-- High Angle of Departure Cmpts, Both Sides, Tmbrwlf/Airwlf	1
44-40-1020	-- Vents, Cmpts, Louvers (Ea)	2
44-11-5160	Whl Well Cmpt, Ahd of Whls Left Side, Tmbrwlf/Airwlf	1
44-10-1600	-- Whl Well Cmpt, Sngl SCBA, Poly Tube, SST Dr, (Fire Shopp)	1
44-10-6000	-- Whl Well Cmpt, SCBA Cmpt Straps	1
44-11-5360	Whl Well Cmpt, Bhnd Whls Left Side, Tmbrwlf/Airwlf	1
44-10-1600	-- Whl Well Cmpt, Sngl SCBA, Poly Tube, SST Dr, (Fire Shopp)	1
44-10-6000	-- Whl Well Cmpt, SCBA Cmpt Straps	1
44-11-5560	Whl Well Cmpt, Ahd of Whls Right Side, Tmbrwlf/Airwlf	1
44-10-1600	-- Whl Well Cmpt, Sngl SCBA, Poly Tube, SST Dr, (Fire Shopp)	1
44-10-6000	-- Whl Well Cmpt, SCBA Cmpt Straps	1
44-11-5760	Whl Well Cmpt, Bhnd Whls Right Side, Tmbrwlf/Airwlf	1
44-10-1600	-- Whl Well Cmpt, Sngl SCBA, Poly Tube, SST Dr, (Fire Shopp)	1
44-10-6000	-- Whl Well Cmpt, SCBA Cmpt Straps	1
90-02-1554	Ladder Mtg, Hyd Rack, Center Mt Lo Pro 1.0, Passenger Side, Twlf	1
90-02-0520	-- Controls, Mtg, Equipment Rack, Rear Body Face	1
90-02-1265	-- Equipment Rack, Covering, Support Arms, Pntd to Match Body	1
90-02-5352	Fldg Attic Ladder Mtng, On Hyd Rack, Twlf/Xfire/RXT	1
90-03-3100	Ladder, Roof, Duo-Safety, 10' Alum 775-A	1
90-07-4060	Ladder, Ext, Duo-Safety, 22' Alum, 3 Sect 925-A	1
90-08-2600	Ladder, Attic, Duo-Safety, 10' Alum, Fold 585-A	1
90-16-5430	Pike Pole Mtg, On Hyd Ladder Rack, Ea, EXT	2
90-16-6100	Pike Poles   Provided by Rosenbauer	1
90-23-1300	-- Hook, Roof NY, w/ Grips, 6-ft, Fire Hooks Unlmt	1
90-23-1500	-- Hook, Roof NY, w/ Grips, 10-ft, Fire Hooks Unlmt	1
90-25-7120	Suction Hose Tray, Single, Driver Side Over Cmpts (Ea), EXT	1
90-25-7220	Suction Hose Tray, Passenger Side Over Cmpts (Ea), EXT	1
90-25-9100	Suction Hose Provd'd By, Bdy Bldr, MN	1
90-25-3120	-- Suction Hose, Flex, Kochek PVC, 6"x10'-MN	2
90-25-6100	-- Suction Hose Cplgs, Alum, LH FM x RLM	2
33-70-1310	Handrail, Right Rr, Vert, 48", Single	1
33-70-2100	Handrails, Pmpr, Below Hosebed, Horz, 48"	1
33-70-3110	Handrails, Pmpr, Left Top of Bdy Side, Rr, 12", Single	1
44-01-1400	Bdy Trim, Frnt Bdy, Ht of Side Cmpts, Alum T/P	1
44-01-4020	Bdy Trim, Rr Bdy, Smooth Alum for Chevron Stripe, EXT	1
44-02-1120	Rub Rails, Lwr Bdy, EXT, Extrd Alum	1
77-10-1420	Winch, Elect, Warn, Front Mt, 16,500#	1
80-22-2102	Bdy Paint, Tmbrwlf, Sngl Color, EXT	1
80-32-1250	Cmpt Finish, DA Sanded, Up to 8 Cmpts, EXT	1
80-40-1250	Whl Finish, By Chassis Manufacturer	1
80-42-1500	Bdy Paint, Touch Up, 2 oz. Bttl, One Color	1
80-43-2995	-- Blacked Out Items- Line-X/Paint	1
80-50-1700	Lettering, 4" Mylar Gold Leaf, 50 Letters	1
80-70-1300	Stripe, Single Reflective, 4", Straight Design	1
80-75-1600	-- Reflective Stripe Material, White	1
80-72-1100	Stripe, Reflective 3M, Chevron Pattern Entire Rear Red/Yellow	1
80-72-2030	Stripe, Reflective, Cab Door Interiors	1
80-79-1000	NFPA Standing / Walking Surfaces Yellow Safety Tape (NFPA 15.7.1.6)	1
90-01-5900	Wheel Chocks Pair Zico #SAC-44 Folding w/ Mounts	1
90-35-1900	Emrgncy Road Kit - DOT Required	1